DESOCOR® PR1620

Major component

• Composite bottom sealing agent with resin and oil wax.

Property

• The film is soft, translucent and extensible.
• Full and comfortable hand feel.
• Excellent sealing performance, improve water absorption, it smooths and refines the uneven-nap buffer crust.
• Strong off-board performance and good stacking.
• Good adhesion properties without affecting subsequent finishes

Specification

Appearance(25°C):	Milky white liquid
Active matter content (%):	16.0±1.0
pH(25°C):	8.7 ±0.5
Ionicity:	Anionic

Application

• Suitable for a variety of leather for sealing, such as sofa leather, bag leather.
Good sealing effect , the skin surface is flat and uniform, improve the hand feel with keeping softness and fullness

DESOCOR PR1620	100
Water	100

Spray x 1，iron：100°C / 20kg / 6m/s

The information contained in this manual is not a unilateral commitment by our company or a contractual provision. Users are responsible for confirming product suitability under actual conditions.

DESOCOR® PR1620

Safety

- This is not a hazardous chemical.
- Observe all the precautions required for handling chemicals.
- Read attentively and observe all the recommendations in our **Safety Data Sheet**.

Transportation and Storage

- The product has a shelf life of one year if it is stored in its tightly sealed original packaging at temperatures between 5°C and 35°C.
- The product should be stored in a cool and dry place, lidded and keep upright. Avoid direct exposure to the sun or frost.
- This product may be stratified during storage, and the application effect will not be affected if using it after mixing evenly.
- Re-seal the package immediately after using, use up as soon as possible once the package is opened.
- Read attentively and observe all the recommendations in our **Safety Data Sheet**.

The information contained in this manual is not a unilateral commitment by our company or a contractual provision. Users are responsible for confirming product suitability under actual conditions.