DESORAY® DA3120

Major component

• Waterborne acrylic polymer.

Property

• The film formed by it is fine, elastic and rich in extensibility.
• Excellent penetration uniformity and leveling property.
• Excellent resistance to flexing endurance and milling performance.
• Gives leather a natural look and feel.

Specification

Appearance(25°C):	Milk white translucent to opaque liquid
Solid Content, %:	20.0±1.0
pH(10.0% aqueous solution, 25°C):	6.0±1.0
Ionicity:	Anionic

Application

• It can be used in all kinds of leather finishing. It can be used as the main film forming resin in the bottom coating for corrected grain leather, which can effectively improve the loose surface and improve the milling performance. It can be used in full-grain leather to give an excellent gloss and natural appearance.

Safety

• This is not a hazardous chemical.
• Observe all the precautions required for handling chemicals.
• Read attentively and observe all the recommendations in our **Safety Data Sheet**.

The information contained in this manual is not a unilateral commitment by our company or a contractual provision. Users are responsible for confirming product suitability under actual conditions.

DESORAY® DA3120

Transportation and Storage

- The product has a shelf life of one year if it is stored in its tightly sealed original packaging at temperatures between 5°C and 35°C.
- The product should be stored in a cool and dry place, lidded and keep upright. Avoid direct exposure to the sun or frost.
- Re-seal the package immediately after using, use up as soon as possible once the package is opened.
- Read attentively and observe all the recommendations in our **Safety Data Sheet**.

The information contained in this manual is not a unilateral commitment by our company or a contractual provision. Users are responsible for confirming product suitability under actual conditions.