DESOTOP® TU4236

Major component

• Matte modified polyurethane emulsion

Property

• Used for water-based finishing top coat to generate natural matting effect.
• Endow the leather with excellent physical properties.
• Bring a pleasant feeling.

Specification

Appearance(25°C):	White liquid
Solid Content, %:	21.0±1.0
pH(10.0% aqueous solution, 25°C):	8.0±1.0
Ionicity:	Anionic

Application

• Usually used in spraying operations.
• Can be combined with other water-based polyurethane top coatings (such as **DESOTOP TU4255**) to adjust the gloss of the product.
• Can be used together with other additives such as hand-feeling agent, hand-feeling wax to improve the leather's hand feeling.
• Cross-linking agent can be used to improve the physical properties of the finished leather.
• Before use, DESOTOP TU4255, hand-feeling agent, and cross-linking agent must be properly matched according to the target requirements, and spraying experiments should be carried out to confirm the gloss and physical properties.

The information contained in this manual is not a unilateral commitment by our company or a contractual provision. Users are responsible for confirming product suitability under actual conditions.

DESOTOP® TU4236

Safety

- This is not a hazardous chemical.
- Observe all the precautions required for handling chemicals.
- Read attentively and observe all the recommendations in our **Safety Data Sheet**.

Transportation and Storage

- The product has a shelf life of one year if it is stored in its tightly sealed original packaging at temperatures between 5°C and 35°C.
- This product may be stratified in the storage process, stir evenly before use, without affecting the use effect.
- The product should be stored in a cool and dry place, lidded and keep upright. Avoid direct exposure to the sun or frost.
- Re-seal the package immediately after using, use up as soon as possible once the package is opened.
- Read attentively and observe all the recommendations in our **Safety Data Sheet**.

The information contained in this manual is not a unilateral commitment by our company or a contractual provision. Users are responsible for confirming product suitability under actual conditions.