DESOTOP TU4265

Major component

• Aqueous aliphatic polyurethane dispersion

Property

• Suitable for patent leather;offers a transparent, non-tacky,elastic,and high-gloss finish.

• This product forms a medium-soft film with excellent flexural resistance under both ambient and low temperatures.

• Excellent resistance to light and heat.

Specification

Appearance(25°C):	Liquid
Color:	Translucent to Milky
Solid content (%):	34.0±1.0
pH (10% aqueous solution,25°C):	8.0±1.0
Ionicity:	Anionic

Application

• This product can be used alone for roll coating, or mixed with a crosslinking agent to enhance physical properties. It can also be diluted with water for spray application.

Safety

• This is not a hazardous chemical.

• Observe all the precautions required for handling chemicals.

• Read attentively and observe all the recommendations in our **Safety Data Sheet**.

The information contained in this manual is not a unilateral commitment by our company or a contractual provision. Users are responsible for confirming product suitability under actual conditions.

DESOTOP TU4265

Transportation and Storage

- The product has a shelf life of one year if it is stored in its tightly sealed original packaging at temperatures 5-35°C.
- The product should be stored in a cool and dry place，lidded and keep upright. Avoid direct exposure to the sun or frost.
- Re-seal the package immediately after using, use up as soon as possible once the package is opened.
- Read attentively and observe all the recommendations in our **Safety Data Sheet.**

The information contained in this manual is not a unilateral commitment by our company or a contractual provision. Users are responsible for confirming product suitability under actual conditions.